



EDAN ELECTRO POWER

## KUBOTA GENSETS

Power Range: 8.3kVA to 40kVA

Voltage: 230V

Frequency: 50Hz

Phase: 1P2W

GENSET MODEL	Power (kW/kVA)		Engine	Alternator	Dimensions (L x W x H) (mm) & Weight (kg)											
	Prime	Standby	Kubota	Meccalte	Open Type		Eden Type		Super Silent Type							
EKM8.3-1P	6/7.5	6.6/8.3	D1105-BG	ECP28-OS/4A	1460	730	1170	450	1715	900	1235	560	1900	920	1280	780
EKM10.6-1P	7.7/9.6	8.5/10.6	D1105-BG	ECP28-S/4A	1460	730	1170	500	1715	900	1235	580	1900	920	1280	788
EKM14-1P	10/12.5	11/14	V1505-BG	ECP28-M/4A	1500	730	1170	550	1915	900	1235	660	2150	920	1280	859
EKM16.5-1P	12/15	13.2/16.5	D1703-BG	ECP28-2L/4A	1460	730	1170	650	1915	900	1235	750	2150	920	1280	925
EKM22.5-1P	16/20	18/22.5	V2203-BG	ECP28-VL/4A	1650	730	1170	700	2115	900	1235	850	2150	920	1280	988
EKM25-1P	18/23	20/25	V2003-T-BG	ECP32-3S/4B	1650	730	1170	750	2115	900	1235	880	2150	920	1280	1027
EKM32.5-1P	24/30	26/32.5	V3300-BG	ECP32-2M/4B	1910	730	1170	780	2215	1000	1550	980	2300	1120	1750	1265
EKM40-1P	29/36	32/40	V3300-T-BG	ECP32-3L/4B	1910	730	1170	850	2215	1000	1550	1100	2300	1120	1750	1314

GENSET MODEL	Power (kW/kVA)		Engine	Alternator	Dimensions (L x W x H) (mm) & Weight (kg)											
	Prime	Standby	Kubota	Starnford	Open Type		Eden Type		Super Silent Type							
EKS8.3-1P	6/7.5	6.6/8.3	D1105-BG	SOL1-J1	1460	730	1170	450	1715	900	1235	560	1900	920	1280	780
EKS10.6-1P	7.7/9.6	8.5/10.6	D1105-BG	SOL1-S1	1460	730	1170	500	1715	900	1235	580	1900	920	1280	788
EKS14-1P	10/12.5	11/14	V1505-BG	SOL2-K1	1500	730	1170	550	1915	900	1235	660	2150	920	1280	859
EKS16.5-1P	12/15	13.2/16.5	D1703-BG	SOL2-K1	1460	730	1170	650	1915	900	1235	750	2150	920	1280	925
EKS22.5-1P	16/20	18/22.5	V2203-BG	SOL2-U1	1650	730	1170	700	2115	900	1235	850	2150	920	1280	988
EKS25-1P	18/23	20/25	V2003-T-BG	PI144H	1650	730	1170	750	2115	900	1235	880	2150	920	1280	1027
EKS32.5-1P	24/30	26/32.5	V3300-BG	UCI224D	1910	730	1170	780	2215	1000	1550	980	2300	1120	1750	1265
EKS40-1P	29/36	32/40	V3300-T-BG	UCI224E	1910	730	1170	850	2215	1000	1550	1100	2300	1120	1750	1314

Voltage: 400V/230V

Frequency: 50Hz

Phase: 3P4W

GENSET MODEL	Power (kW/kVA)		Engine	Alternator	Dimensions (L x W x H) (mm) & Weight (kg)											
	Prime	Standby	Kubota	Meccalte	Open Type		Eden Type		Super Silent Type							
EKM11	8/10	8.8/11	D1105-BG	ECP28-2VS/4A	1460	730	1170	500	1715	900	1235	580	1900	920	1280	770
EKM14	10/12.5	11/14	V1505-BG	ECP28-OS/4A	1550	730	1170	550	1915	900	1235	680	2150	920	1280	800
EKM16.5	12/15	13.2/16.5	D1703-BG	ECP28-S/4A	1460	730	1170	650	1915	900	1235	700	2150	920	1280	893
EKM22.5	16/20	18/22.5	V2203-BG	ECP28-M/4A	1650	730	1170	700	1915	900	1235	750	2150	920	1280	941
EKM25	18/23	20/25	V2003-T-BG	ECP28-2L/4A	1650	730	1170	750	1915	900	1235	780	2150	920	1280	968
EKM32.5	24/30	26/32.5	V3300-BG	ECP28-VL/4A	1910	730	1170	780	2215	1000	1550	920	2300	1120	1750	1177
EKM40	29/36	32/40	V3300-T-BG	ECP32-3S/4B	1910	730	1170	850	2215	1000	1550	950	2300	1120	1750	1219

GENSET MODEL	Power (kW/kVA)		Engine	Alternator	Dimensions (L x W x H) (mm) & Weight (kg)											
	Prime	Standby	Kubota	Stamford	Open Type		Eden Type		Super Silent Type							
EKS11	8/10	8.8/11	D1105-BG	SOL1-H1	1460	730	1170	500	1715	900	1235	580	1900	920	1280	770
EKS14	10/12.5	11/14	V1505-BG	SOL1-L1	1550	730	1170	550	1915	900	1235	680	2150	920	1280	800
EKS16.5	12/15	13.2/16.5	D1703-BG	SOL1-P1	1460	730	1170	650	1915	900	1235	700	2150	920	1280	893
EKS22.5	16/20	18/22.5	V2203-BG	SOL2-G1	1650	730	1170	700	1915	900	1235	750	2150	920	1280	941
EKS25	18/23	20/25	V2003-T-BG	SOL2-M1	1650	730	1170	750	1915	900	1235	780	2150	920	1280	968
EKS32.5	24/30	26/32.5	V3300-BG	SOL2-P1	1910	730	1170	780	2215	1000	1550	920	2300	1120	1750	1177
EKS40	29/36	32/40	V3300-T-BG	SIL2-K1	1910	730	1170	850	2215	1000	1550	950	2300	1120	1750	1219