

MTU GENSETS

Power Range: 300kVA to 3250kVA

Voltage: 400V/230V

Frequency: 50Hz

Phase: 3P4W

The genset is powered by MTU which used high-pressure common-rail EFI technology, greatly improved combustion efficiency and lowered fuel consumption and emission. It can provide strong driving force and run long hours continuously. As high power generator with the function of fault self-diagnose and remote control, it is widely used in the area of industry, railway, power equipment and so on. MTU engines are manufactured in Germany or China in accordance with the MTU global quality standards. The global service networks of EDAN and MTU can provide our customers with reliable and guaranteed service.

GENSET MODEL	Power (kW/kVA)		Engine	Alternator	Dimensions (L x W x H) (mm) & Weight (kg)					
	Prime	Standby	MTU	Meccalte	Open Type		Eden Type		Super Silent Type	
EMM300	220/275	240/300	6R1600G10F	EC038-2L/4A	3200×1090×1920	3200	4350×1130×2120	4300	4100×1300×2140	4350
EMM330	240/300	264/330	6R1600G20F	EC038-2L/4A	3200×1090×1920	3200	4350×1130×2120	4300	4100×1300×2140	4350
EMM385	280/350	308/385	8V1600G10F	EC038-3L/4A	3315×1450×1750	3619	4930×1600×2280	5317	4600×1600×2280	5417
EMM440	320/400	352/440	8V1600G20F	EC040-1S/4B	3315×1450×1750	3619	4930×1600×2280	5317	4600×1600×2280	5417
EMM500	360/450	400/500	10V1600G10F	EC040-2S/4B	3315×1450×1750	3711	4930×1600×2280	5409	4600×1600×2280	5509
EMM550	400/500	440/550	10V1600G20F	EC040-3S/4B	3315×1450×1750	3711	4930×1600×2280	5409	4600×1600×2280	5509
EMM660	480/600	528/660	12V1600G10F	EC040-1.5L/4B	3350×1450×1750	3831	4930×1600×2280	5529	4600×1600×2280	5629
EMM715	520/650	572/715	12V1600G20F	EC040-2L/4B	3350×1450×1750	3831	4930×1600×2280	5529	4600×1600×2280	5629
EMM880	640/800	704/880	12V2000G65	EC043-1S/4A	4100×1580×2130	7000	20' container	10800		
EMM1000	728/910	800/1000	16V2000G25	EC043-2S/4A	4500×1580×2280	8000	20' container	12000		
EMM1100	808/1010	880/1100	16V2000G65	EC043-1M/4A	4500×1580×2280	8000	20' container	12000		
EMM1265	920/1150	1012/1265	18V2000G65	EC043-2M/4A	4700×1900×2430	9000	40' container	15000		
EMM1375	1000/1250	1100/1375	18V2000G26F	EC043-2L/4A	4700×1900×2430	9000	40' container	15000		
EMM1540	1120/1400	1232/1540	12V4000G23R	EC043-VL/4A	5200×2100×2660	11500	40' container	18000		
EMM1650	1200/1500	1320/1650	12V4000G23	EC046-1S/4A	5300×2100×2660	12000	40' container	18500		
EMM1815	1320/1650	1452/1815	12V4000G23	EC046-1.5S/4A	5300×2100×2660	12000	40' container	18500		
EMM1980	1440/1812	1584/1980	12V4000G63	EC046-2S/4A	5350×2100×2660	12200	40' container	18700		
EMM2250	1640/2050	1800/2250	16V4000G23	EC046-1L/4A	5800×2630×2880	12600	40' container	18600		
EMM2530	1840/2300	2024/2530	16V4000G63	EC046-1.5L/4A	5900×2630×2880	13000	40' container	19000		
EMM2750	2000/2500	2200/2750	20V4000G23	EC046-2L/4A	5900×2630×2880	15000	40' container	21200		
EMM3080	2240/2800	2464/3080	20V4000G63	EC046-VL/4A	6100×2700×2800	16000	40' container	22000		
EMM3250	2400/3000	2600/3250	20V4000G63L	LSA53.2 M9 (Leroy-somer)	6500×2700×2800	16000	40' container	22000		

GENSET MODEL	Power (kW/kVA)		Engine	Alternator	Dimensions (L x W x H) (mm) & Weight (kg)					
	Prime	Standby	MTU	Stamford	Open Type		Eden Type		Super Silent Type	
EMS300	220/275	240/300	6R1600G10F	S4L 1D-D41	3200×1090×1920	3200	4350×1130×2120	4300	4100×1300×2140	4350
EMS330	240/300	264/330	6R1600G20F	S4L 1D-D41	3200×1090×1920	3200	4350×1130×2120	4300	4100×1300×2140	4350
EMS385	280/350	308/385	8V1600G10F	S4L 1D-E41	3315×1450×1750	3619	4930×1600×2280	5317	4600×1600×2280	5417
EMS440	320/400	352/440	8V1600G20F	S4L 1D-F41	3315×1450×1750	3619	4930×1600×2280	5317	4600×1600×2280	5417
EMS500	360/450	400/500	10V1600G10F	S4L 1D-G41	3315×1450×1750	3711	4930×1600×2280	5409	4600×1600×2280	5509
EMS550	400/500	440/550	10V1600G20F	HCI544D	3315×1450×1750	3711	4930×1600×2280	5409	4600×1600×2280	5509
EMS660	480/600	528/660	12V1600G10F	HCI544E	3350×1450×1750	3831	4930×1600×2280	5529	4600×1600×2280	5629
EMS715	520/650	572/715	12V1600G20F	HCI544F	3350×1450×1750	3831	4930×1600×2280	5529	4600×1600×2280	5629
EMS880	640/800	704/880	12V2000G65	S6L1D-C4	4100×1580×2130	7000	20' container	10800		
EMS1000	728/910	800/1000	16V2000G25	S6L1D-D4	4500×1580×2280	8000	20' container	12000		
EMS1100	808/1010	880/1100	16V2000G65	S6L1D-E4	4500×1580×2280	8000	20' container	12000		
EMS1265	920/1150	1012/1265	18V2000G65	S6L1D-H4*	4700×1900×2430	9000	40' container	15000		
EMS1375	1000/1250	1100/1375	18V2000G26F	S6L1D-H4*	4700×1900×2430	9000	40' container	15000		
EMS1540	1120/1400	1232/1540	12V4000G23R	S6L1D-H4*	5200×2100×2660	11500	40' container	18000		
EMS1650	1200/1500	1320/1650	12V4000G23	PI734C	5300×2100×2660	12000	40' container	18500		
EMS1815	1320/1650	1452/1815	12V4000G23	PI734D	5300×2100×2660	12000	40' container	18500		
EMS1980	1440/1812	1584/1980	12V4000G63	PI734E	5350×2100×2660	12200	40' container	18700		
EMS2250	1640/2050	1800/2250	16V4000G23	PI734H	5800×2630×2880	12600	40' container	18600		
EMS2530	1840/2300	2024/2530	16V4000G63	PI734H	5900×2630×2880	13000	40' container	19000		
EMS2750	2000/2500	2200/2750	20V4000G23	LVS1804S	5900×2630×2880	15000	40' container	21200		
EMS3080	2240/2800	2464/3080	20V4000G63	LVS1804S	6100×2700×2800	16000	40' container	22000		
EMS3250	2400/3000	2600/3250	20V4000G63L	LVS1804T	6500×2700×2800	16000	40' container	22000		